

PT6YT

Self-priming Trash Pump

Large discharge volume, long running time

With a large discharge volume and a long running time, the self-priming centrifugal pump PT6 is perfect for demanding applications. The pump is driven by a sturdy and powerful Yanmar diesel engine with an electric starter. The impeller, made of ductile iron, and the mechanical seals, made of silicon-carbide, ensure a high level of wear resistance and long operational duration with minimal maintenance necessity.

Highlights

- Shimmable wear plate for longevity and durability
- Quick-release clean out cover
- Central lifting eye
- Powerful Yanmar engine
- Control panel and battery

Technical Data

Mechanical - Output Details

Flow rate max.	4,150.0 l/min
Pump pressure max.	2.2 bar
Solid diameter max.	50.0 mm
Suction head max.	7.5 m
Delivery height max.	23.0 m

Mechanical Details

Length	2,155.0 mm
Width	1,491.0 mm
Height	1,714.0 mm
Operating weight	870.0 kg
Intake-/Pressure socket-dia.	152.0 mm

Engine

Engine type	Diesel engine
Tank capacity	90.0 l
Power rating max.	17.3 kW
Engine speed 1	2,700.0 1/min
Consumption at Speed 1	5.0 l/h
Run Time at Speed 1	18.0 hrs

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com

Available engines

Yanmar 3TNV80F-NXDWN1

Cooling	Water-cooling
Engine type	Diesel engine
Engine operating mode	four-stroke
Cylinder	3
Cylinder capacity	1,267 cm^3
Kraftstofftyp	Diesel EN 590
Oil filling max.	3.4 l
Power rating max.	18.4 kW
Engine speed (Power max.)	3,000 PL
Exhaust-gas limit	EPA Tier 4 final
Starter type	E-starter
Engine Manufacturer	Yanmar

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com