



## BRS90

### Round plate

The combination of vibratory rammer and single-direction vibratory plate

With the BRS90, Wacker Neuson offers a maneuverable and compact round plate, excellent for compaction performance in confined environments, for example in trenches. Thanks to the optimized round plate, perfect finishes can be achieved on edges and in corners. The machine can be maneuvered easily by the sturdy guide handle. Here, low hand-arm-vibrations ensure high working comfort.

#### Highlights

- Optimally shaped round plate
- Combination of vibratory rammer and vibratory plate

#### Technical Data

##### ■ Mechanical - Output Details

Centrifugal force	14 kN
Area capacity	645.0 m <sup>2</sup> /h
Forward running	25.0 m/min
Gradeability	32.0 %
Vibrations (Hz)	90.0 Hz

Height 1,053.0 mlai

Height Cover frame 1,053.0 mlai

Thickness Baseplate 12.0 mlai

Operating weight 90.0 kg

##### ■ Engine

Effective power 3.6 KW

Nominal Engine speed 3,600.0 1/min

##### ■ Environment Data

HAV summation (average value) 2.1 ms

##### ■ Mechanical Details

Length Baseplate	425.0 mlai
Width	430.0 mlai
Width Baseplate	430.0 mlai

## Available engines

### **Honda GX160H2-SX-3-SD**

Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder	1
Cylinder capacity	163 cm <sup>3</sup>
Kraftstofftyp	Gasoline
Fuel consumption	1.40 L/hr
Effective power	3.60 kW
Nominal Engine speed	3,600 PL
Standard (Effective power)	ISO 3046 IFN
Operating power	3.5 kW
Operating Engine speed	3,500 PL
Standard (Operating power)	ISO 3046 IFN
Starter type	Recoil starter
Engine Manufacturer	Honda
First oil change	100 h