



AS68ve/25

Electric rammers

Optimum adjustment of the impact rate to different soil conditions thanks to the speed adjustment.

The battery-powered rammer allows the operator to work completely free of emissions. The battery-powered rammer is a win for soil compaction in trenches and inner cities as well as lightening the load for the operator and environment on every construction site. One battery charge is enough to finish all the tasks of an average workday. The battery can be easily changed without tools and can be used for a variety of other Wacker Neuson construction equipment.

Highlights

- Speed adjustment
- Maintenance-free electric motor
- BatteryOne battery system
- Ergonomic guide handle
- Easy start
- Carry handle on the ramming shoe
- Active cooling
- No exhaust emissions

Technical Data

■ Electrical - Output Details

Nominal current	44.00 A
Nominal voltage	51.0 V
Nominal power [P]	2.24 KW

Weight 59.00 kg

Operating weight 69.0 kg

Stroke at tamper 51.0 mm

■ Motor

Motor type Asynchronous motor

■ Mechanical - Output Details

Number of blows	680.0 1/min
Area capacity	165.0 m2/h
Forward Running	11.0 m/min
Power of impact	18.0 kN

Degree of protection IP23D

Storage temperature range -30 - 50 °C

Sound power LWA, guaranteed 108.0 dB(A)

Sound power LWA (Standard) EN 500-4

■ Mechanical Details

Length	625.0 mm
Length Ramming Shoe	340.0 mm
Width	360.0 mm
Width Ramming Shoe	250.0 mm
Height	925.0 mm

HAV summation (average value) 9.4 m/s²

HAV summation (Standard) EN 500-4

■ Operating Fluids

Oil specification SAE 10W-40

Oil volume 0.700 l