

AR64/6/042

External vibrators for consolidation of prefabricated concrete factories

Highly resilient in use

The AR64 shows its strengths particularly in continuous use: It offers vibration-proof and heat-resistant electric motor windings, highly resilient special bearings and maximum operational reliability. And that even under the toughest operating conditions. The best thing about it: Its minimal maintenance requirements and long service life. A complete professional in the precast plant.

MAT: 5100004216

Highlights

- Sturdy design

Technical Data

Electrical - Output Details

Nominal current	21.50 A
Nominal voltage	42.0 V
Nominal frequency	200.0 Hz
Nominal power [P]	1.20 kW
Phase	3.0 ~

Mechanical - Output Details

Centrifugal force	10 kN
Vibrations	6,000.0 1/min
Vibrations (Hz)	100.0 Hz
Centrifugal force max.	19.03 kN

Mechanical Details

Length	245.0 mm
Width	155.0 mm
Height	188.0 mm
Weight	13.80 kg
Unbalanced mass/side pos1	5.0
Unbalanced mass/side pos2	3.0
Hole pattern length	120.0 mm
Hole pattern width	120.0 mm
Hole pattern hole diameter	16.0 mm

Motor

Motor type	Asynchronous motor

Environment Data

Protection class	III / Safety extra-low voltage
Degree of protection	IP65

Electrical System

Breaker Switch On/Off	no
Operating indicator	No
Adjusting frequency	No
Integrated transformer	No

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com