





## **GV7000A**

## **Portable Generators**

Three performance classes for reliable power supply

The generators in the GV series are cost-effective synchronous generators offering a reliable power supply even throughout continuous operation. The GV series includes models in three different performance categories as well as AC and three-phase designs. In addition to application on construction sites, the portable generators can equally be used for industrial, commercial and agricultural applications.

## Highlights

- Sturdy protective frame
- Large tank with long running time
- Compact dimensions
- Honda four-stroke motor
- No grounding necessary

## **Technical Data**

Electrical - Output Details	
Aggregate continuous power 1~ (COP)	5.0 KW
Aggregate maximum power (MAX)	5.4 KW
Mechanical Details	
Length	729.0 mm
Width	500.0 mm
Height	536.0 mm
Operating weight	79.0 kg
Generator	
Generator type	NSM K100 G
Output current 1~	25.1 A
Output voltage	230.0 V
Output frequency	50.0 Hz

Efficiency factor 1~	0.9 cos φ
Nominal speed	3,000.0 1/min
Phase	1.0 ~
Earthing system	Electrical separation
Environment Data	
Degree of protection	IP23M
Sound power LWA, guaranteed	97.0 dB(A)
Electrical System	
Main Circuit Breaker Rating	25.0 A
Available voltages 1~	230.0 V
Receptacle Type	CEE 3P 32A 6h 230V 50Hz
Number of Sockets	2.0

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.