



**WACKER
NEUSON**
all it takes!

Dumpers

Track and Wheeled



Track Dumpers

Track dumpers are the ideal material handling solution for smaller jobs that need the advantages of a tracked machine. The mini-track dumpers can fit through narrow garden gates and doorways, making them an ideal choice for confined area landscape, concrete, demolition and residential applications.

Wheeled Dumpers - Traditional and Dual View

Articulated wheel dumpers are excellent for moving bulk materials. With our Dual View dumpers, the operator can quickly and comfortably change the seat and console position to keep the task front and center. The entire operating platform rotates 180 degrees, giving the best view while working or driving the machine.

Performance Data

Wheeled Dumpers

	Unit	DW30	DW30 Concrete edition	DW50	DV60	DV90	DV100
Max. operating power at operating speed	hp rpm	45.3 @ 2,200	45.3 @ 2,200	59.7 @ 2,300	74.2 @ 2,200	74.2 @ 2,200	74.2 @ 2,200
Engine type		Perkins 403J-E17T, liquid-cooled, 3-cylinder turbo diesel engine.		Deutz TD 2.2, liquid-cooled, 3-cylinder turbo diesel engine.	Deutz TD2.9 L4, liquid-cooled, 4-cylinder, diesel engine.		
Fuel tank capacity	gal	11.9	11.9	15.9	21.1	21.1	21.1
Travel speed	mph	0-15.5	0-15.5	0-15.5	0-18.6	0-18.6	0-18.6
Standard tires		11.50/80 x 15.3, Mitas tractor tread		12.5-18/16, Mitas universal tread	405/70-20 (Mitas, MPT-01)	500/60-22.5 (Alliance, Flotation 331)	
Final drive		Hydrostatic transmission, permanent 4-wheel drive, electronic driving direction switch.					
Working brake		Hydrostatic / Wet multidisk					
Pump capacity Operating / Drive	gal/min	8.2 / 26.2	8.2 / 26.2	14 / 32.5	19.4 / 32.6	19.4 / 32.6	19.4 / 32.6
Operating pressure Operating / Drive	psi	2,901 / 6,498	2,901 / 6,498	3,191 / 7,252	3,481 / 7,252	3,481 / 7,252	3,481 / 7,252
Hydraulic tank capacity	gal	11.1	11.1	10.6	15.9	15.9	15.9
Height ROPS/CAB	in	112.6 / 105.1	112.6 / -	110.8 / -	135.2 / 115.2	- / 119.3	- / 119.3
Width	in	70.1	70.1	75.8	87.3	96.6	98.6
Length	in	166.3	199.3	177.0	175.1	182	183.5
Max safe payload	lb	6,614	6,614	11,023	13,228	19,841	22,046
Skip capacity	leveled	1.67		2.62	3.1	4.3	5.4
	heaped	2.29		3.47	4.1	5.7	6.5
	water	262	317	3.49	423	542	674
Transport weight ROPS / CAB	lbs	5,545 / 5,895	5,675 / -	7,580 / -	8,715 / 9,469	- / 10,814	- / 10,869

Track Dumpers

	Unit	DT08 Gasoline, front tip	DT10 Diesel, Front tip with self-loading shovel	DT10 Diesel, Swivel tip	DT10 Diesel, Front tip platform	DT12 Gasoline Swivel or front tip	DT15 Diesel, 3-way side-tipping platform	DT15 Diesel, swivel tip
Engine model/ make		Honda GX270	Kubota Z482-EF02	Kubota Z482-EF02	Kubota Z482-EF02	Vanguard	Kubota D902-EF03	Kubota D902-EF03
Performance	hp	9.1	13	13	13	23	20	20
Travel Speed	mph	2.5	2.5	2.5	2.5	5.6	2.5	2.5
Ground pressure - empty	psi	2.3	2.6	2.6	2.6	2.6	4.0	4.0
Ground pressure - loaded	psi	4.8	7.4	7.4	7.4	7.4	7.3	7.3
Shipping weight	lbs	1,301	1,532	1,708	1,301	1,345 - 1,650	2,799	2,932
Max. machine payload	lbs	1,764	2,645	2,645	2,645	2,646	3,307	3,307
Skip capacity - heaped	cu ft ³	13.7	15.8	16.2	10.6	17.8	24.4	26.8
Skip capacity - leveled	cu ft ³	11.8	13.9	15.2	7.4	15.2	18.7	19.4
Skip capacity - water	gal	43.9	45.7	63.4	-	110.4	137.4	108.3
Length	in	65.3	71.8	71.8	74.1	81.3	104	105.3
Undercarriage width	in	31.1	31.1	31.1	31.1	31.1	42.5	42.5
Width of skip	in	27.5	27.5	28.7	31.7	32.5	40.2	43.3
Skip length	in	51.9	53.4	56.1	47.2	62.3	60.9	60.5
Max. height, skip raised	in	72.6	76.7	83.1	56.3	70.7	80.3	93.7
Skip type		Front tip	Front tip with self-loading shovel	Swivel tip	Front tip platform	Swivel or Front Tip	3-way side-tipping platform	Swivel tip



DT08



DT10



DT12



DT15



DW30



DW50



DV60



DV90



DV100

