



## PS2-1500

### Submersible Pump

Heavy-duty and durable for demanding dewatering tasks

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

#### Highlights

- Variety of models
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Oil lifter for reliable lubrication in any situation
- Safe to run dry
- Steel sleeve reduces wear of the shaft

#### Technical Data

##### ■ Electrical - Output Details

Nominal current	15.40 A
Nominal voltage	230.0 V
Nominal frequency	50.0 Hz
Phase	1.0 ~

Width 187.0 mm

Height 600.0 mm

Operating weight 33.0 kg

Intake-/Pressure socket-dia. 50.0 mm

##### ■ Motor

Nominal speed 2,900.0 1/min

##### ■ Mechanical - Output Details

Flow rate max.	440.0 l/min	■ Electrical System
Solid diameter max.	6.0 mm	Length Cable 10.0 m
Delivery height max.	17.5 m	Cable cross-section 4.0 mm <sup>2</sup>

##### ■ Mechanical Details

Length	187.0 mm
--------	----------