



PSA2 500

Submersible Pump

Automatic, lightweight pumps, perfect for any task

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Highlights

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

■ Mechanical - Output Details

Flow rate max.	236.0 l/min
Solid diameter max.	6.0 mm
Delivery height max.	12.0 m

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

■ Mechanical Details

Length	222.0 mm
Width	186.0 mm
Height	304.0 mm
Operating weight	10.0 kg

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

■ Motor

Nominal power	0.48 KW
---------------	---------

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.