



5507

Telehandler

A combination of flexibility and efficiency

The Kramer 5507 telescopic loader offers the robustness of a wheel loader combined with the advantages of a telescopic loader. The model is particularly characterized by the stacking height of up to 7 m and 5.5 t payload. The powerful Deutz engine, in combination with the standard ecospeedPRO travel drive, ensures high performance. In addition, the different working modes of the Smart Handling overload system allow, above all, safety and comfort.

Hydraulics: Load-sensing hydraulic pump with a discharge volume of max. 187 l/min for quick load cycles

Operating concept: 7" LCD display, all-in-one joystick and jog dial control element for easy machine control

Payload: Stacking height of over 7 m and a payload of 5.5 t with telescopic loading system

Comfortable cabin: Stress-free working and increased levels of concentration, even on longer working days

Frame: Torsion-resistant frame in box profile design with lateral support for the telescopic arm

Technical Data

■ Standard engine data

Engine manufacturer	Deutz
Drive output	115 kW
Drive output	156 PS
at max. rpm	2,300 U/min
Cylinder capacity	4,038 cm ³
Exhaust standard level	V
Exhaust aftertreatment	DOC / DPF / SCR

Lift capacity (max.) 56.7 kN

■ Filling levels

Tank capacity for hydraulic oil	100 l
Tank capacity for urea solution	12 l

■ Drive system

Travel speed Standard	0-40 km/h
Travel speed Option 1	0-20 km/h
Travel speed Option 2	0-30 km/h
Differential lock	100% self-locking differential connectable in the front axle

■ Weights

Payload (max.)	5,500 kg
Payload at max. reach	2,000 kg
Payload at max. stacking height	4,000 kg
Stacking height (max.)	7,017 mm
Payload max. (LSP 500 mm)	5,500 kg
Operating weight	9,500 - 10,500 kg
Thrust force (max.)	67.6 kN

Lift capacity (max.) 56.7 kN


■ Steering

Steering angle max. 38 degree

■ Noise characteristic values

Guaranteed sound power level LwA (cabin)	101 dB(A)
Measured sound power level LwA	97.1 dB(A)
Sound pressure level at the operator's ear	72 dB(A)

Dimensions



A1	Total length	4,985 mm
A2	Total length with bucket	6,160 mm
B1	Total width without bucket	2,500 mm
C1	Front track: rear	2,065 mm
D1	Total height	2,570 mm
D2	Total height with rotating beacon	2,740 mm
E1	Cab width	990 mm
F1	Wheel base center	2,950 mm
G1	Ground clearance under axle and transmission, wading depth	418 mm
H1	Distance center rear wheel to rear	950 mm
I1	Rear approach angle (slope angle)	35 °
J1	Dumping angle	45 °
K1	Max. stacking height	7,017 mm
J2	Dumping angle	41 °
L1	Load-over height: retracted	4,518 mm
L2	Load-over height: extended	6,835 mm
M1	Dumping height: retracted	3,865 mm
M2	Dumping height: extended	6,183 mm
N1	Dumping width: extended	495 mm
O1	Tele extension length: retracted	5,287 mm
O2	Tele extension length: extended	7,604 mm
P1	Total height telescopic arm mounting in frame	1,761 mm
Q1	Distance center front wheel to bucket leading edge	2,260 mm
Q2	Distance center front wheel bearing quick change frame	935 mm
R1	Bucket pivot point: retracted	5,092 mm
R2	Bucket pivot point: extended	7,409 mm
S1	Turning radius outer edge wheels	4,240 mm
S2	Turning radius outer edge bucket	5,265 mm
T1	Entry height cab floor	975 mm

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.