

PS2 800

Submersible Pump

These high performance single-phase submersible pumps are ideal for job sites needing fast, dependable, low level water pumping.

Pump can start in low water levels when it is primed through the discharge port. No matter how large or small the job. Wacker Neuson submersible pumps offer the versatility and durability contractors need for light dewatering. Suitable for most outlets, these pumps offer big pump features for small pump investment.

MAT: 5000620436

Highlights

- Top discharge for continuous operation and motor cooling
- Durable mechanical seals
- Kink-free multi-directional discharge coupling
- Heavy-duty strain relief power cord
- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

Mechanical - Output Details

Flow rate max.	81.9 gal/mi
Solid diameter max.	0.2 in
Delivery height max.	59.1 Foot

Mechanical Details

Length	7.6 in
Width	7.4 in
Height	13.4 in
Operating weight	29.1 lb
Intake-/Pressure socket-dia.	2.0 in

Motor

Nominal power	0.75 kW
Nominal current	5.3 A
Nominal voltage	220.0 V
Nominal frequency	60.0 Hz
Nominal speed	3,300.0 1/min

Environment Data

Temperature limit borrowed liquid	104.0 - 32.0 °F

Electrical System

Length Cable	49.2 Foot
Cable cross-section	0.0 Inch2
Cable definition	PVC Sheath

Shipping and Storage

Length for shipping	18.7 in
Width for shipping	10.5 in
Height for shipping	10.2 in
Shipping weight	36.2 lb

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com