



APU3360e

Reversible vibratory plates with battery drive

Maintenance-free and efficient thanks to the **DireX** direct drive

The APU series is a technological milestone: As the first reversible vibratory plates worldwide, the battery-powered vibratory plates of the APU series are particularly efficient and completely maintenance-free as a result of the DireX direct drive. The emission-free drive and the low overall height make it the ideal compaction equipment for shoring in trenches. The APU series has excellent operational properties on soil and asphalt, and provides a high degree of operating comfort, for example through the sturdy, integrated wheel set and the continuously adjustable forward and reverse travel speeds.

Highlights

- Starts with a push of a button
- No exhaust emissions
- Low overall height
- All-round protection due to steel cover
- Efficient drive system DireX
- Battery One battery system
- Center pole
- Intuitive guide bar with continuously adjustable speed.
- Integrated wheel set

Technical Data

Mechanical - Output Details

Mechanical - Output Details		Height	1,188.0 mm
Centrifugal force	33 kN	Height Cover frame	618.0 mm
Area capacity	648.0 m2/h	Thickness Baseplate	10.0 mm
Forward Running	18.0 m/min	Weight	229.00 kg
Gradeability	48.0 %	Ground clearance	618.0 mm
Standard Support Plate	without Support Plate	Environment Data	
Mechanical Details			
		HAV summation (Standard)	EN 500-4
Length Baseplate	703.0 mm	HAV summation (Standard) Electrical System	EN 500-4
	703.0 mm 600.0 mm	· · · · · · · · · · · · · · · · · · ·	EN 500-4 23.0 min
Length Baseplate		Electrical System	

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.