

PS2-500

Submersible Pump

Heavy-duty and durable for demanding dewatering tasks

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Highlights

- Variety of models
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Safe to run dry

Technical Data

Electrical - Output Details

Nominal voltage	230.0 V
Nominal frequency	50.0 Hz
Starting current Idle running	7.0 A
Starting current full load	2.9 A
Phase	1.0 ~

Mechanical - Output Details

Flow rate max.	220.0 l/min
Solid diameter max.	6.0 mm
Delivery height max.	11.0 m

Mechanical Details

Length	185.0 mm
Width	185.0 mm
Height	355.0 mm
Operating weight	9.5 kg
Intake-/Pressure socket-dia.	50.0 mm

Motor

Nominal speed	3,000.0 1/min

Electrical System

Length Cable	10.0 m
Cable cross-section	1.0 mm²

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com