



## PSA2 500

### Submersible Pump

Automatic, lightweight pumps, perfect for any task

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

#### Highlights

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

#### Technical Data

##### ■ Mechanical - Output Details

Flow rate max.	62.3 gal/mi
Solid diameter max.	0.2 "
Delivery height max.	39.4 Foot

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

##### ■ Mechanical Details

Length	8.7 "
Width	7.3 "
Height	12.0 "
Operating weight	22.0 lb

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

##### ■ Motor

Nominal power	0.48 KW
---------------	---------

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

Nominal current 6.1 A

Nominal voltage 110.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min