



**WACKER  
NEUSON**  
*all it takes!*

# DS70

## Diesel Rammer




## The professional for extreme compaction work

The diesel rammer by Wacker Neuson rounds off your diesel fleet. The DS70 is a well-balanced machine with compact dimensions and low CO emissions. This also makes it well-suited for compaction work in trenches. The DS70 offers strong performance for compaction of cohesive, mixed and granular soils.

### Highlights

#### Extreme performance efficiency

With its high compaction performance, time and costs can be saved.



#### Just one lever for starting, idling and stopping

The vibratory rammer can be operated very comfortably using just one lever. The choke is integrated in the lever.



### Technical information

|  | Units             | DS70      |
|--|-------------------|-----------|
| <b>Mechanical Details - Output Details</b> |                   |           |
| Number of blows                            | 1/min             | 667       |
| Area capacity                              | m <sup>2</sup> /h | up to 174 |
| Forward Running                            | m/min             | up to 8.8 |
| Power of impact                            | kN                | 21        |
| <b>Mechanical Details</b>                  |                   |           |
| Length                                     | mm                | 740       |
| Length Ramming Shoe                        | mm                | 340       |
| Width                                      | mm                | 370       |
| Width Ramming Shoe                         | mm                | 330       |
| Height                                     | mm                | 1,000     |
| Weight                                     | kg                | 85        |
| Operating weight                           | kg                | 86.4      |
| Stroke length                              | mm                | 75        |
| <b>Engine</b>                              |                   |           |
| Engine type                                |                   | Yanmar    |
| <b>Environment Data</b>                    |                   |           |
| Operating temperature range                | °C                | -10 - 40  |
| Sound power LWA, guaranteed                | dB(A)             | 108       |
| Sound power LWA (Standard)                 |                   | EN 500-4  |
| HAV summation (average value)              | m/s <sup>2</sup>  | 11.9      |
| HAV summation (Standard)                   |                   | EN 500-4  |

The construction equipment warranty terms and policy (Terms) covers all Wacker Neuson products sold by and in the Wacker Neuson Pty Ltd region of Australia and New Zealand. Product Registration is required to activate extended warranty period on eligible machines. Machines not registered within 30 days of purchase will have the Statutory 1 Year/1,000 hours warranty period.

The images, equipment and data shown may differ from the range of products currently available in your country.

Optional equipment may be shown under certain circumstances subject to a surcharge in the price. The right to make any changes is reserved.

[www.wackerneuson.com](http://www.wackerneuson.com)