





E3000

Hydronic Heater

dual reeled hydronic heater for the toughest jobs.

Engineered for reliable performance and trouble-free starts for up to 140 hours of run time, the E3000 will provide maximum flow and ensure consistent heat delivery for thawing and curing applications. The E3000 thaws or cures up to 6,000 sq. ft. With accessories this heater will cure up to 18,000 sq. ft. or provide 535,000 cu. ft. of dry heat at 83% efficiency, the highest in the industry.

Water-cooling

Highlights

- Powerful positive displacement pumps
- Dual hose reels

Technical Data

| Nominal current 20.00 A Nominal voltage 120.0 V Mechanical Details Length 4,600.0 mm Gross Axle Weight Rating 2,304.0 kg Width 2,300.0 mm Height 2,400.0 mm Operating weight 4,076.0 kg Dry Weight 3,406.0 kg Gross vehicular weight 4,076.0 kg Lift Bail - quantity 1.0 Length hose 914.0 m Generator Insulation class H Output current 1~ 30.0 A Output voltage 120.0 V Output frequency 60.0 Hz |
|---|
| Mechanical Details Length 4,600.0 mm Gross Axle Weight Rating 2,304.0 kg Width 2,300.0 mm Height 2,400.0 mm Operating weight 4,076.0 kg Dry Weight 3,406.0 kg Gross vehicular weight 4,076.0 kg Lift Bail - quantity 1.0 Length hose 914.0 m Generator Insulation class H Output current 1~ 30.0 A Output voltage 120.0 V Output frequency 60.0 Hz |
| Length 4,600.0 mm Gross Axle Weight Rating 2,304.0 kg Width 2,300.0 mm Height 2,400.0 mm Operating weight 4,076.0 kg Dry Weight 3,406.0 kg Gross vehicular weight 4,076.0 kg Lift Bail - quantity 1.0 Length hose 914.0 m Generator Insulation class Output current 1~ 30.0 A Output voltage 120.0 V Output frequency 60.0 Hz |
| Gross Axle Weight Rating 2,304.0 kg Width 2,300.0 mm Height 2,400.0 mm Operating weight 4,076.0 kg Dry Weight 3,406.0 kg Gross vehicular weight 4,076.0 kg Lift Bail - quantity 1.0 Length hose 914.0 m Generator Insulation class H Output current 1~ 30.0 A Output voltage 120.0 V Output frequency 60.0 Hz |
| Width 2,300.0 mm Height 2,400.0 mm Operating weight 4,076.0 kg Dry Weight 3,406.0 kg Gross vehicular weight 4,076.0 kg Lift Bail - quantity 1.0 Length hose 914.0 m Generator Insulation class Insulation class H Output current 1~ 30.0 A Output voltage 120.0 V Output frequency 60.0 Hz |
| Height 2,400.0 mm Operating weight 4,076.0 kg Dry Weight 3,406.0 kg Gross vehicular weight 4,076.0 kg Lift Bail - quantity 1.0 Length hose 914.0 m Generator Insulation class H Output current 1~ 30.0 A Output voltage 120.0 V Output frequency 60.0 Hz |
| Operating weight 4,076.0 kg Dry Weight 3,406.0 kg Gross vehicular weight 4,076.0 kg Lift Bail - quantity 1.0 Length hose 914.0 m Generator Insulation class H Output current 1~ 30.0 A Output voltage 120.0 V Output frequency 60.0 Hz |
| Dry Weight 3,406.0 kg Gross vehicular weight 4,076.0 kg Lift Bail - quantity 1.0 Length hose 914.0 m Generator Insulation class H Output current 1~ 30.0 A Output voltage 120.0 V Output frequency 60.0 Hz |
| Gross vehicular weight 4,076.0 kg Lift Bail - quantity 1.0 Length hose 914.0 m Generator Insulation class H Output current 1~ 30.0 A Output voltage 120.0 V Output frequency 60.0 Hz |
| Lift Bail - quantity 1.0 Length hose 914.0 m Generator Insulation class H Output current 1~ 30.0 A Output voltage 120.0 V Output frequency 60.0 Hz |
| Length hose 914.0 m Generator Insulation class H Output current 1~ 30.0 A Output voltage 120.0 V Output frequency 60.0 Hz |
| Generator Insulation class H Output current 1~ 30.0 A Output voltage 120.0 V Output frequency 60.0 Hz |
| Insulation class H Output current 1~ 30.0 A Output voltage 120.0 V Output frequency 60.0 Hz |
| Output current 1~ 30.0 A Output voltage 120.0 V Output frequency 60.0 Hz |
| Output voltage 120.0 V Output frequency 60.0 Hz |
| Output frequency 60.0 Hz |
| |
| |
| Nominal power 6.0 KW |
| Voltage Regulation - Steady State 6.0 % |
| Generator Manufacturer Mecc Alte |
| Generator specification Brushless with capacitor |
| Genset yes |

Engine

Cooling

| Cooming | Trator cooming |
|------------------------------|---------------------------|
| Engine type | Diesel engine |
| Cylinder | 3.0 |
| Cylinder capacity | 1,028.0 cm3 |
| Operating Engine speed | 1,800.0 1/min |
| Engine Manufacturer | Kohler |
| Environment Data | |
| Operating temperature range | 38 - 82 °C |
| Electrical System | |
| Temperature monitor | digital |
| Operating Fluids | |
| Oil volume | 3.800 |
| Fuel specification | Winter Blend Diesel No. 2 |
| Run Time (75 % Prime Load) | 108.0 hrs |
| Fuel Tank capacity | 871.0 I |
| Utilizable tank capacity | 840.0 |
| Fuel Consumption no genset | 10.4 L/hr |
| Fuel Consumption with genset | 12.7 L/hr |
| Run Time (100 %) | 81.0 hrs |
| Chassis | |
| Brake | Electric brake |
| Tongue Weight, min. | 384.0 kg |
| Tongue Weight, max. | 521.0 kg |

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Shipping and Storage

Shipping weight with Trailer

4,076.0 kg

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.