



APS1135we

Electric vibratory plates

Excellent handling and maneuverability on soil and asphalt

The APS series is distinguished by its outstanding handling capabilities. Moving and turning these vibratory plates on fresh asphalt is unsurpassed in comfort and produces clean finishes with no marks. Even clean finishes at curbs are easy to produce due to the angular side edges of the base plate. The guide handle responds precisely to steering movements while still achieving low hand-arm vibrations of less than 5 m/s², which makes long and comfortable working conditions possible. Because of the direct drive, the APS series does not require V-belts and is therefore maintenance-free.

Highlights

- Starts with a push of a button
- Maintenance-free electric motor
- Removable battery
- Base plate optimized for perfect work results
- Excellent turning ability and control with simultaneously low HAV
- Efficient drive system DireX

Technical Data

■ Mechanical - Output Details

| | |
|------------------------|----------------------------|
| Centrifugal force | 2,473 lbf |
| Area capacity | 5,877.1 ft ² /h |
| Forward Running | 1.4 fps |
| Gradeability | 46.6 % |
| Standard Support Plate | without Support Plate |

■ Mechanical Details

| | |
|------------------|--------|
| Length Baseplate | 23.6 " |
| Width | 13.8 " |
| Width Baseplate | 13.8 " |

| | |
|---------------------|-----------|
| Height | 26.1 " |
| Height Cover frame | 26.1 " |
| Thickness Baseplate | 0.2 " |
| Weight | 160.94 lb |
| Underclearance | 26.1 " |

■ Environment Data

| | |
|-------------------------------|------------------------|
| HAV summation (average value) | 16.1 ft/s ² |
| HAV summation (Standard) | EN 500-4 |

■ Electrical System

| | |
|-----------------|----------|
| Battery runtime | 90.0 min |
|-----------------|----------|