



DPU5260Hehb+ US

Medium-weight vibratory plates

Efficient and precise for trench and surface compaction

The medium-heavy, reversible vibratory plates offer the perfect combination of high forward and reverse speeds and outstanding compaction performance. They have been specially developed for the requirements of trench and surface compaction and enable efficient and precise compaction of different soil types and structures. With their modern and ergonomic user interface, they offer maximum convenience and make work easier, resulting in a noticeable increase in productivity. The diesel-powered Pro version also boasts a powerful machine control system with innovative features: Bluetooth connectivity via smartphone app, compaction control as standard and optional Compamatic and telematics functionality. Numerous machine diagnostics functions also simplify service and maintenance, ensuring smooth operation and a long service life for your machine.

Highlights

- Optimum control and ergonomics
- Low HAV (< 2.5 m/s²)
- Compamatic
- Digital machine control
- Easy cleaning due to open base plate

Technical Data

Mechanical - Output Details

Centrifugal force	11,690 lbf
Area capacity	10,850.1 ft ² /h
Forward Running	1.5 fps
Vibrations (Hz)	69.0 Hz

Mechanical Details

Length Baseplate	38.0 "
Width	23.6 "
Width Baseplate	23.6 "
Height	57.0 "

Height Cover frame	34.5 "
Thickness Baseplate	0.6 "
Operating weight	948.0 lb
Underclearance	34.5 "

Engine

Effective power	10.2 hp
Nominal Engine speed	3,000.0 1/min

Environment Data

HAV summation (Standard)	EN 500-4
--------------------------	----------