



PS3 1500

Submersible Pump

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Pump can start in low water levels when it is primed through the discharge port. No matter how large or small the job. Wacker Neuson submersible pumps offer the versatility and durability contractors need for light dewatering. Suitable for most outlets, these pumps offer big pump features for small pump investment.

Highlights

- Built-in thermal protection prevents motor damage
- Lightweight, compact design
- Durable mechanical seals
- Heavy-duty strain relief power cord
- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

Mechanical - Output Details

Flow rate max.	111.0 gal/mi
Solid diameter max.	0.3 "
Delivery height max.	68.9 Foot

Mechanical Details

Length	9.4 "
Width	9.4 "
Height	22.4 "
Operating weight	63.5 lb
Intake-/Pressure socket-dia.	3.1 "

Motor

Nominal power	1.50 KW
Nominal current	23.0 A
Nominal voltage	110.0 V

Nominal frequency	60.0 Hz
Nominal speed	3,440.0 1/min

Environment Data

Temperature limit borrowed liquid	104.0 - 32.0 °F
-----------------------------------	-----------------

Electrical System

Length Cable	32.8 Foot
Cable cross-section	0.0 Inch ²
Cable definition	PVC Sheath

Shipping and Storage

Length for shipping	13.6 "
Width for shipping	13.0 "
Height for shipping	28.0 "
Shipping weight	77.2 lb