



PS2 800

Submersible Pump

These high performance single-phase submersible pumps are ideal for job sites needing fast, dependable, low level water pumping.

Pump can start in low water levels when it is primed through the discharge port. No matter how large or small the job. Wacker Neuson submersible pumps offer the versatility and durability contractors need for light dewatering. Suitable for most outlets, these pumps offer big pump features for small pump investment.

Highlights

- Top discharge for continuous operation and motor cooling
- Built-in thermal protection prevents motor damage
- Durable mechanical seals
- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

■ Mechanical - Output Details

Flow rate max. 81.9 gal/mi

Nominal frequency 60.0 Hz

Solid diameter max. 0.2 "

Nominal speed 3,300.0 1/min

Delivery height max. 59.1 Foot

Temperature limit borrowed liquid 104.0 - 32.0 °F

■ Mechanical Details

Length 7.6 "

Length Cable 49.2 Foot

Width 7.4 "

Cable cross-section 0.0 Inch²

Height 13.4 "

Cable definition PVC Sheath

Operating weight 29.1 lb

■ Shipping and Storage

Intake-/Pressure socket-dia. 2.0 "

Length for shipping 18.7 "

■ Motor

Nominal power 0.75 KW

Width for shipping 10.5 "

Nominal current 10.1 A

Height for shipping 10.2 "

Nominal voltage 110.0 V

Shipping weight 36.1 lb