



**WACKER  
NEUSON**  
*all it takes!*

## PS4-3703

### Submersible Pump

powerful and reliable for construction site dewatering

The robust PS series three-phase submersible pumps can handle wastewater containing solids up to a diameter of 20 mm. They feature a high flow rates and high heads, making them ideal for applications where it is important to dry out construction sites quickly and reliably. These high-quality pumps are extremely durable and easy to use. The PS series are also offered in lightweight aluminum models and automatic versions.

### Highlights

- Model variations
- Optional motor protection plug for three-phase pumps
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Oil lifter for reliable lubrication in any situation
- Safe to run dry
- Steel sleeve reduces wear of the shaft

### Technical Data

#### ■ Electrical - Output Details

Nominal current	7.70 A
Nominal voltage	400.0 V
Nominal frequency	50.0 Hz
Phase	3.0 ~

#### ■ Mechanical - Output Details

Flow rate max.	1,440.0 l/min
Solid diameter max.	8.5 mm
Delivery height max.	18.0 m

#### ■ Mechanical Details

Length	285.0 mm
--------	----------

Width 250.0 mm

Height 675.0 mm

Operating weight 62.0 kg

Intake-/Pressure socket-dia. 100.0 mm

#### ■ Motor

Nominal speed 2,850.0 1/min

#### ■ Electrical System

Length Cable 20.0 m

Cable cross-section 1.5 mm<sup>2</sup>