


AR34/3/400

External vibrator

The expert for bulk material

Wacker Neuson external vibrators deliver excellent results when filling, consolidating, transporting and sifting bulk material Its maximum 3,000 rpm ensures that bulk material is moving continuously, does not clump and is thus optimally prepared for later use. There are a variety sizes and versions of Wacker Neuson external vibrators for loosening, separating and transporting.

Highlights

- Asynchronous motor with stable speed
- Adjustable eccentric weight discs

Technical Data

Electrical - Output Details

Nominal current	0.75 A
Nominal voltage	400.0 V
Nominal frequency	50.0 Hz
Nominal power [P]	0.40 kW
Phase	3.0 ~

Mechanical - Output Details

Centrifugal force	3 kN
Vibrations	3,000.0 1/min
Vibrations (Hz)	50.0 Hz
Centrifugal force max.	3.47 kN

Mechanical Details

Length	295.0 mm
Width	151.0 mm
Height	134.0 mm
Weight	7.00 kg
Unbalanced mass/side pos1	32.0
Unbalanced mass/side pos2	0.0
Hole pattern length	120.0 mm
Hole pattern width	120.0 mm
Hole pattern hole diameter	18.0 mm

Motor

Motor type	Asynchronous motor

Environment Data

Protection class	I / Protective earthing
Degree of protection	IP67

Electrical System

Breaker Switch On/Off	no
Operating indicator	No
Adjusting frequency	No
Integrated transformer	No

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com