



GS6500G

Portable Generator of the G series

Reliable power solutions for demanding use

The G Series generators are engineered to meet the demands of professional applications, offering high load starting, high power output, durability and cost-effectiveness. These generators feature with strong air filtration system and a large fuel tank, ensuring longer operation and superior reliability. With a robust frame, the G Series is built to withstand harsh environments and continuous use.

Highlights

- Sturdy protective frame
- Large tank with long running time
- Reliable Loncin engine
- Automatic Voltage Regulation (AVR)
- Compact dimensions

Technical Data

Mechanical Details

Length	695.0 mm
Width	546.0 mm
Height	550.0 mm
Dry Weight	87.0 kg

Generator

Insulation class	• A
Output current 1~	50.0 A
Output frequency	60.0 Hz
Efficiency factor 1~	1.0 cos φ
Nominal speed	3,600.0 1/min
Phase	1.0 ~
Generator specification	• AVR with Brushes
Voltage 1~	120.0 V
Maximum Output	6,500.0 W
Continuous Output	6,000.0 W

Engine

Engine type	• Gasoline engine
-------------	-------------------

Tank capacity	30.0 l
---------------	--------

Environment Data

Degree of protection	• IP23
Sound power LWA, guaranteed	97.0 dB(A)
Sound power LWA (Standard)	• 2000/14/EG

Electrical System

Circuit Breaker Amperage AC	40.0 A
Available voltages 1~	120.0 V
Breaker Switch On/Off	• 1 Pole
CE Performance Class	• G1
Type of battery	• LiFePO4
Installed capacity	1.6 Ah
Receptacle Type	• NEMA5-20R,Duplex,125V,20A

Operating Fluids

Fuel consumption (50 % Pime Load)	2.3 L/hr
Run Time (50 % Prime Load)	10.0 hrs