



PG3A Dewatering Pump

Efficiently extract clear water

With its self-priming centrifugal pumping action and overall compact size, the pump is ideal for the contractor with the need for temporary water removal.

Highlights

- Pump out vanes on back of impeller.
- Cast iron impeller and volute for long life and minimal service
- Carbon ceramic mechanical seal

Technical Data

■ Mechanical - Output Details

Flow rate max.	264.2 gal/mi
Solid diameter max.	0.3 "
Suction head max.	24.6 Foot
Delivery height max.	98.4 Foot

■ Mechanical Details

Length	20.3 "
Width	15.9 "
Height	18.1 "
Operating weight	68.3 lb
Intake-/Pressure socket-dia.	3.0 "

■ Engine

Cooling	• air cooling
---------	---------------

Engine type	• Gasoline engine
Cylinder	1.0
Cylinder capacity	9.9 Inch ³
Fuel	• Gasoline
Fuel consumption	0.5 GPH US
Tank capacity	1.0 gal US
Oil filling max.	0.2 gal US
Power rating max.	4.8 hp
Engine speed (Power max.)	3,600.0 1/min
Operating Engine speed	3,600.0 1/min
Engine Manufacturer	• Honda
Fuel consumption at full power	0.5 GPH US
Running time at 100%	2.1 hrs