



## LTT6 Light Tower

Powerful and Compact

The LTT4 and LTT6 light towers offer a smaller footprint and the long-lasting LED's deliver exceptional light coverage for a variety of applications where temporary lighting is needed. The units are equipped with auxiliary power which adds to the versatility of these machines.

### Highlights

- LED Lights
- Programmable Controller
- Compact Design
- Standard Auxiliary Power
- Telescopic Vertical Mast

### Technical Data

#### ■ Mechanical Details

Length	100.9 "
Width	47.5 "
Height	100.3 "
Operating weight	1,554.3 lb
Mast height max.	23.0 Foot

Cylinder 3.0

Cylinder capacity 62.7 Inch<sup>3</sup>

Fuel Winter Blend Diesel No. 2

Tank capacity 52.4 gal US

Effective power 11.3 hp

Operating Engine speed 1,800.0 1/min

Exhaust-gas limit EPA Tier 4 final

Engine Manufacturer Kohler

#### ■ Electrical System

Lighting appliances 320W (LED)

Bulb power 320.0 W

#### ■ Operating Fluids

Fuel consumption (Lights only) 0.3 GPH US

Run Time (Lights only) 173.4 hrs

#### ■ Engine

Cooling	Water-cooling
Engine type	Diesel engine