

FUH20/1/042

Portable frequency converter

Light and compact - perfect for small construction sites

At only 8.9 kg weight, the frequency converter FUH20 is a real lightweight and thus easy to transport on the construction site. The high-frequency technology not only saves weight, but also provides reliable and stable output. It has already been time-tested and proven to be absolutely reliable in other industries and is now used by Wacker Neuson for frequency converters.

Highlights

- Compact dimensions, low weight

Technical Data

Electrical - Output Details

Nominal current	7.80 A
Nominal voltage	230.0 V
Nominal frequency	50.0 Hz
Output current	20.0 A
Output voltage	42.0 V
Output frequency	200.0 Hz
Phase	1.0 ~
Output Phase	3.0 ~

Mechanical Details

Length	545.0 mm
Width	138.0 mm
Height	241.0 mm
Weight	8.90 kg

Environment Data

Protection class	I / Protective earthing
Degree of protection	IP44

Electrical System

Breaker Switch On/Off	no
Operating indicator	yes
Adjusting frequency	No
Length Cable	1.5 m
Kind of plug	CEE 7/7 (Plug Type EF)
Receptacle Type	CEE 3P 32A 4H 50V 100-200Hz
Number of Sockets	1.0

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com