

WP1550e

Battery-powered, single-direction vibratory plate

Battery-powered compaction professional

The WP1550e is the powerful professional for long-term application. The battery-powered vibratory plate works without any direct exhaust gas emissions, which protects the operator and the environment in equal measure. Thanks to the centrally affixed guidance rail and the specially-designed base plate, the vibratory plate can be effortlessly turned. Thanks to the DireX direct drive, the Wp1550e works without V-belts and is therefore completely maintenance-free.

MAT: 5100062425

Highlights

- Optimally shaped base plate
- Efficient drive system DireX
- No exhaust emissions
- Control handle
- BatteryOne battery system

Technical Data

Mechanical - Output Details

Centrifugal force	15 kN
Area capacity	870.0 m²/h
Forward Running	29.0 m/min
Gradeability	46.6 %
Standard Support Plate	without Support Plate

Mechanical Details

Length Baseplate	582.0 mm
Width	500.0 mm
Width Baseplate	500.0 mm
Height	963.0 mm
Height Cover frame	551.0 mm
Thickness Baseplate	10.0 mm
Weight	95.00 kg
Underclearance	551.0 mm

Environment Data

HAV summation (average value)	3.6 m/s²
HAV summation (Standard)	EN 500-4

Electrical System

BOB5 Runtime	30.0 min
BOB10 Runtime	60.0 min
BOB14 Runtime	80.0 min

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com