



BS68-4A/28

4-stroke Rammers

Outstanding work performance and long service life

Wacker Neuson's 4 stroke rammers characterized by excellent work performance. The long shoe stroke, the high ramming frequency, high impact energy and fast travel speed ensure first-class work results. Well thought-out functions make the use of the 4 stroke rammers even more operator-friendly, extend their service life, and minimize maintenance.

Highlights

- Large stroke, high impact force
- Just one lever for starting, idling and stopping
- Efficient air filter
- Ergonomic guide handle
- Low oil warning indicator
- Large stroke, high impact force
- Efficient air filter
- Ergonomic guide handle

Technical Data

Mechanical - Output Details

Number of blows	689.0 1/min
Area capacity	202.0 m ² /h
Forward Running	12.0 m/min
Power of impact	19.0 kN

Mechanical Details

Length	662.0 mm
Length Ramming Shoe	340.0 mm
Width	347.0 mm
Width Ramming Shoe	280.0 mm
Height	950.0 mm
Weight	69.00 kg
Operating weight	70.0 kg

Stroke at tamper 63.0 mm

Environment Data

Operating temperature range	-10 - 40 °C
Sound power LWA, guaranteed	108.0 dB(A)
Sound power LWA (Standard)	EN 500-4
HAV summation (average value)	9.4 m/s ²
HAV summation (Standard)	EN 500-4

Electrical System

Operating elements	Pushbutton OFF
--------------------	----------------

Operating Fluids

Oil specification	SAE 10W-40
Oil volume	0.900 l

Available engines

■ Honda GXR120RT-KR-W1-SD

Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder	1
Cylinder capacity	121 cm ³
Fuel	Gasoline
Fuel consumption	1.00 L/hr
Tank capacity	3.00 l
Effective power	2.30 KW
Nominal Engine speed	3,600 PL
Standard (Effective power)	SAE J1349
Operating power	2.7 KW
Operating Engine speed	3,950 PL
Standard (Operating power)	ISO 3046-1
Starter type	Recoil starter
Engine Manufacturer	Honda
Engine Designation	GXR120RT-KR-W1-SD