



IRSEN58/250GV

High-frequency internal vibrators

Concrete consolidation with comfortable operation

The Wacker Neuson IRSEN series of high-frequency internal vibrators offer a short protection hose and low vibration handle. The ergonomically designed handle with vibration damping offers a high degree of comfort during operation. Wacker Neuson's IRSEN high-quality internal vibrators offer a variety of features and benefits.

Highlights

- Handle (Low Vib)
- High-performance electric motor with stable speeds
- Made in Germany
- Sturdy design

Technical Data

■ Electrical - Output Details	
Nominal current	3.00 A
Nominal voltage	250.0 V
Nominal frequency	200.0 Hz
Nominal power [P]	1.05 KW
Phase	3.0 ~
■ Mechanical - Output Details	
Amplitude at air	2.500 mm
Vibrations	12,000.0 1/min
Vibrations (Hz)	200.0 Hz
Mechanical Details	
Length Hose	0.8 m

Weight	12.10 kg
Rubber cap	yes
Motor	
Motor type	Asynchronous motor
Environment Data	
Protection class	I / Protective earthing
Degree of protection	IP67
Electrical System	
Breaker Switch On/Off	Yes
Integrated transformer	No
Length Cable	8.0 m
Kind of plug	CEE-Plug 4P 16A 250V 10H

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes