



## DPU5260Hehcpb+

## Medium-weight vibratory plate 300-600kg NextGen

Efficient and precise for trench and surface compaction

The medium-heavy, reversible vibratory plates offer the perfect combination of high forward and reverse speeds and outstanding compaction performance. They have been specially developed for the requirements of trench and surface compaction and enable efficient and precise compaction of different soil types and structures. With their modern and ergonomic user interface, they offer maximum convenience and make work easier, resulting in a noticeable increase in productivity. The diesel-powered Pro version also boasts a powerful machine control system with innovative features: Bluetooth connectivity via smartphone app, compaction control as standard and optional Compamatic and telematics functionality. Numerous machine diagnostics functions also simplify service and maintenance, ensuring smooth operation and a long service life for your machine.

## Highlights

- Optimum control and ergonomics
- Low HAV (< 2.5 m/s²)
- Compamatic
- Digital machine control
- Easy cleaning due to open base plate

## **Technical Data**

Mechanical - O	output Details
----------------	----------------

Centrifugal force	52 kN
Area capacity	1,008.0 m2/h
Forward Running	28.0 m/min
Vibrations (Hz)	69.0 Hz
Mechanical Details	
Length Baseplate	965.0 mm
Width	600.0 mm
Width Baseplate	470.0 mm
Height	1,449.0 mm

Height Cover frame	877.0 mm
Thickness Baseplate	15.0 mm
Operating weight	437.0 kg
Ground clearance	877.0 mm
Engine	
Effective power	7.1 KW
Nominal Engine speed	2,700.0 1/min
Environment Data	
HAV summation (average value)	2.5 m/s2
HAV summation (Standard)	EN 500-4

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.