

DPU 3050H US

Reversible vibratory plate

Maximum compaction in the tightest spaces

The DPU3050H is one of the powerful all-rounders for paving work, gardening and landscaping, as well as for maintenance work on roads, paths and parking lots. Like all vibratory plates in the 25 - 37 kN class from Wacker Neuson, it features a robust, integrated wheel set. As a result, this class of equipment offers mobility on the construction site that is unique in the market. Due to its compact design and great maneuverability, the DPU3050H is ideal for compacting trenches, sidewalks and other confined areas. Well thought-out details make it the ideal compactor for continuous professional use.

Highlights

- Compact dimensions, high performance
- Integrated wheel set
- Sturdy and durable

Technical Data

Mechanical - Output Details

Centrifugal force	30 kN
Area capacity	570.0 m²/h
Forward Running	19.0 m/min
Gradeability	46.6 %
Vibrations (Hz)	90.0 Hz

Mechanical Details

Length Baseplate	703.0 mm
Width	500.0 mm
Width Baseplate	500.0 mm
Height	1,101.0 mm
Height Cover frame	777.0 mm
Thickness Baseplate	10.0 mm
Operating weight	181.0 kg
Underclearance	777.0 - 887.0 mm

Engine

Effective power	4.2 kW
Nominal Engine speed	2,800.0 1/min

Environment Data

HAV summation (average value)	3.6 m/s²
HAV summation (Standard)	EN 500-4

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com