



RD45-140c DPF

Tandem roller

Powerful and versatile

The articulated RD45 is a powerful roller that offers balanced weight distribution on the front and rear drum which provides very even compaction results. It offers a high degree of driving stability and is easy to maneuver. Additionally, the excellent view compacted area and the large drum diameter contribute to first-class results. The ROPS roll-over protective structure, which can be folded away to the rear for transport, makes for a safer working environment.

Highlights

- Combination roller: Rear axle with rubber tires
- Ergonomic work platform
- Uniform operating concept
- Large line-of-sight, compact construction

Technical Data

■ Mechanical - Output Details

Gradeability	30.0 %
Gradeability max. (without vibration)	40.0 %
Travel speed	0.0 - 11.0 km/h
Compaction force Level I (front)	85 kN
Compaction force Level II (front)	60 kN
Vibration frequency Level I (front)	60.0 Hz
Vibration frequency Level II (front)	51.0 Hz
Amplitude Level I (front)	0.5100 mm
Amplitude Level II (front)	0.3100 mm
Centrifugal force Level I (front)	64 kN

■ Mechanical Details

Length	2,965.0 mm
Width	1,506.0 mm
Height	2,590.0 mm
Operating weight	4,050.0 kg
Dry Weight	3,795.0 kg
Gross vehicular weight	4,220.0 kg
Curb clearance right	63.0 mm
Curb clearance left	63.0 mm
Operating width	1,380.0 mm
Ground clearance Middle	305.0 mm

Turning radius inside	2,650.0 mm
Operating weight with roll-over protective structure	4,050.0 kg
Operating weight with cabin	4,300.0 kg
Wheelbase	1,950.0 mm
Operating weight, max.	5,250.00 kg
Curb clearance (left)	720.0 mm
Curb clearance (right)	720.0 mm
Total height with cabin	2,720.0 mm
Empty weight with cabin	4,055.0 kg
Empty weight with ROPS	3,795.0 kg
Turning radius outside	4,030.0 mm

■ Engine

Cylinder capacity	2,434.0 cm ³
Effective power	37.4 KW
Nominal Engine speed	2,700.0 1/min
Standard (Effective power)	ISO 14396
Starter battery Voltage	12.0 V
Battery capacity (nom. value)	95.0 Ah
Engine Manufacturer	Kubota
Engine Designation	V2403-CR

■ Environment Data

Sound level LpA	88.0 dB(A)
-----------------	------------

Sound power LWA, guaranteed	104.0 dB(A)
Exhaust aftertreatment	DOC-DPF
Catalyst	yes
Particle filter	yes
CO (NRTC)	0.1 g/KWh
CO2 (NRTC)	834.6 g/KWh
HC + NOx (NRTC)	3.0 g/KWh
PM (NRTC)	0.0 g/KWh

■ **Operating Fluids**

Water tank capacity	285.0 l
Fuel Tank capacity	73.0 l

■ **Chassis**

Pendulum angle +/-	8.0 °
Width over tires (rear)	1,276.0 mm
Number of tires (rear)	4.0
Wheel size (rear)	10.5/80-17
Wheel load per tire (rear)	448.8 kg