



DPS2050H

Single-direction vibratory plates

Powerful and versatile on all surfaces

The DPS single-direction vibratory plate provides powerful compaction results on soil and asphalt and is ideally suited for use on top and base layers. It was designed for tough, long-term application on the construction site. The diesel engine, equipped with large power reserves, the wear-resistant base plate from ductile graphite iron (GJS 700), we well as the maintenance-free and durable exciter bearing all contribute to the plate's long life and durability. The easy to reach throttle lever and vibration damped guide handle offer a high degree of operating comfort.

Highlights

- Excellent turning ability and control with simultaneously low HAV
- Wide, ergonomic handle
- Control handle
- Wheel set quickly ready for use
- Paving pad device easy to mount
- Permanently lubricated ball bearings

Technical Data

■ Mechanical - Output Details

Centrifugal force	20 kN
Area capacity	660.0 m ² /h
Forward Running	22.0 m/min
Gradeability	36.4 %
Vibrations (Hz)	98.0 Hz

Height Cover frame 663.0 mm

Thickness Baseplate 9.0 mm

Operating weight 102.0 kg

Underclearance 663.0 mm

■ Engine

Effective power 3.4 KW

Nominal Engine speed 3,400.0 1/min

■ Environment Data

HAV summation (average value) 3.1 m/s²

HAV summation (Standard) EN 500-4

■ Mechanical Details

Length Baseplate	599.0 mm
Width	500.0 mm
Width Baseplate	500.0 mm
Height	663.0 mm

Available engines

Hatz 1B20-7-333A

Cooling	air cooling
Engine type	Diesel engine
Engine operating mode	four-stroke
Cylinder	1
Cylinder capacity	243 cm ³
Fuel	Diesel EN 590
Fuel consumption	0.40 L/hr
Tank capacity	3.00 l
Starter type	Recoil starter
Engine Manufacturer	Hatz