



BPU3750Ats

Reversible vibratory plate

Maximum compaction in the tightest spaces

The lightweight reversible vibratory plates are powerful and versatile making them ideal for base preparation, gardening, landscaping and maintenance work on streets, roads and parking lots. The Wacker Neuson vibratory plates in the 25-37 kN class come equipped with a sturdy, integrated wheel set. This unique feature provides mobility on the construction site.

Highlights

- Compact dimensions, high performance
- Integrated wheel set
- Sturdy and durable

Technical Data

■ Mechanical - Output Details

Centrifugal force	8,318 lbf
Area capacity	7,750.1 ft ² /h
Forward Running	1.3 fps
Gradeability	46.6 %
Vibrations (Hz)	90.0 Hz

Height Cover frame 30.6 "

Thickness Baseplate 0.4 "

Operating weight 529.1 lb

Underclearance 30.6 - 34.9 "

■ Engine

Effective power 7.5 hp

Nominal Engine speed 2,800.0 1/min

■ Environment Data

HAV summation (average value) 8.2 ft/s²

HAV summation (Standard) EN 500-4

■ Mechanical Details

Length Baseplate	27.7 "
Width	19.7 "
Width Baseplate	19.7 "
Height	43.3 "

Available engines

Honda GX270-UT2X-QA-4-SD

Cylinder capacity	16.5 Inch3
Fuel consumption	0.4 GPH US
Tank capacity	1.4 gal US
Effective power	6.8 PS
Operating power	6.8 PS
Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder	1
Fuel	Gasoline
Standard (Effective power)	SAE J1349
Standard (Operating power)	ISO 3046 IFN
Starter type	Recoil starter
Engine Manufacturer	Honda