

GV7003A

Portable Generators of the GV series

Three performance classes for reliable power supply

The generators in the GV series are cost-effective synchronous generators offering a reliable power supply even throughout continuous operation. The GV series includes models in three different performance categories as well as AC and three-phase designs. In addition to application on construction sites, the portable generators can equally be used for industrial, commercial and agricultural applications.

MAT: 5100002155

Highlights

- Sturdy protective frame
- Large tank with long running time
- Compact dimensions
- Honda four-stroke motor
- No grounding necessary

Technical Data

Electrical - Output Details

Aggregate cont. Power1~ (COP)	3.2 kW
Aggr. pwr time limited 1~(LTP)	3.4 kW
Aggregate cont. Power3~ (COP)	5.7 kW
Aggregate maximum power (MAX)	6.0 kW

Mechanical Details

Length	729.0 mm
Width	500.0 mm
Height	536.0 mm
Operating weight	86.0 kg

Generator

Generator type	NSM T100 SC
Output current 1~	14.1 A
Output voltage	400.0 V
Output frequency	50.0 Hz
Efficiency factor 1~	0.9 cos φ
Nominal speed	3,000.0 1/min
Efficiency factor 3~	0.8 cos φ
Phase	3.0 ~
Earthing system	Electrical separation
Output current 3~	10.8 A

Environment Data

Degree of protection	IP23M
Sound power LWA, guaranteed	97.0 dB(A)

Electrical System

Main Circuit Breaker Rating	10.0 A
Available voltages 3~	400.0 V
Available voltages 1~	230.0 V
Receptacle Type	CEE 3P 16A 6h 230V 50Hz
Number of Sockets	3.0

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com