





AR 34/3/230 v

External vibrators for consolidation of prefabricated concrete factories

The long-distance runner

Long service life and minimal maintenance—the AR34 is a longdistance runner when it comes to concrete consolidation. And not only that: the AR34 performs with maximum reliability and safety in the toughest operating conditions—even in 24-hour continuous applications. Vibration-proof and heat-resistant windings of the electric motor (plastic sealing, class H up to 180°C) as well as the extremely robust special bearings contribute to the long run time.

Highlights

■ Sturdy design

Technical Data

-		ombalanood maoo, oldo pooz	0.0
Nominal current	1.30 A	Motor	
Phase	3.0 ~	Motor type	Asynchronous m
Mechanical - Output Details		Environment Data	
Centrifugal force max.	6.930 kN	Protection class	I / Protective ear
Mechanical Details		Degree of protection	IP67
Length	295.0 mm	Electrical System	
Width	151.0 mm	Breaker Switch On/Off	no
Height	134.0 mm	Operating indicator	No
Weight	6.27 kg	Adjusting frequency	No
Unbalanced mass/side pos1	21.0	Integrated transformer	No

Unbalanced mass/side pos2 0.0

Motor type	Asynchronous motor
Environment Data	
Protection class	I / Protective earthing
Degree of protection	IP67
Electrical System	
Breaker Switch On/Off	no
Operating indicator	No
Adjusting frequency	No
Integrated transformer	No

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.