

AP2560e

Single direction vibratory plate

Soil and asphalt compaction without emissions

Wacker Neuson's AP2560e battery-operated vibratory plate offers a completely emission-free work site. This protects the operator and the environment. With its high speed and wide base plate, the AP2560e is ideal for compacting large areas. The base plate, made of heavy-duty nodular cast iron, and stable bearings contribute to the machine's long service life.

MAT: 5100048488

Highlights

- Starts with a push of a button
- Maintenance-free electric motor
- No exhaust emissions
- Low energy costs
- Removable battery

Technical Data

Mechanical - Output Details

Centrifugal force	26 kN
Area capacity	756.0 m²/h
Forward Running	21.0 m/min
Gradeability	46.6 %
Standard Support Plate	without Support Plate

Mechanical Details

Length Baseplate	650.0 mm
Width	600.0 mm
Width Baseplate	600.0 mm
Height	500.0 mm
Height Cover frame	500.0 mm
Thickness Baseplate	8.0 mm
Weight	133.00 kg
Underclearance	500.0 mm

Environment Data

Operating temperature range	0
HAV summation (average value)	4.4 m/s²
HAV summation (Standard)	EN 500-4

Electrical System

BOB10 Runtime	32.0 min
BOB14 Runtime	55.0 min

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com