



DPU 2560H-TS

Reversible vibratory plate

Fast and efficient when compacting paving stones.

The lightweight reversible vibratory plates are powerful and versatile making them ideal for base preparation, gardening, landscaping and maintenance work on streets, roads and parking lots. The Wacker Neuson vibratory plates in the 25-37 kN class come equipped with a sturdy, integrated wheel set. This unique feature provides mobility on the construction site.

Highlights

- Top-speed version
- Compact dimensions, high performance
- Integrated wheel set
- Sturdy and durable

Technical Data

■ Mechanical - Output Details

| | |
|-------------------|-------------------------|
| Centrifugal force | 25 kN |
| Area capacity | 756.0 m ² /h |
| Forward Running | 21.0 m/min |
| Gradeability | 46.6 % |
| Vibrations (Hz) | 90.0 Hz |

■ Mechanical Details

| | |
|--------------------|------------|
| Length Baseplate | 703.0 mm |
| Width | 600.0 mm |
| Width Baseplate | 600.0 mm |
| Height | 1,097.0 mm |
| Height Cover frame | 736.0 mm |

| | |
|---------------------|------------------|
| Thickness Baseplate | 10.0 mm |
| Operating weight | 171.0 kg |
| Underclearance | 736.0 - 846.0 mm |

■ Engine

| | |
|----------------------|---------------|
| Effective power | 3.1 KW |
| Nominal Engine speed | 2,800.0 1/min |

■ Environment Data

| | |
|-------------------------------|----------------------|
| HAV summation (average value) | 2.7 m/s ² |
| HAV summation (Standard) | EN 500-4 |

■ Electrical System

| | |
|----------------------|-------|
| Coding options | 0 |
| Remote Control Range | 0.0 m |

Available engines

■ Hatz 1B20-7-327D

| | |
|-----------------------|---------------------|
| Cooling | air cooling |
| Engine type | Diesel engine |
| Engine operating mode | four-stroke |
| Cylinder | 1 |
| Cylinder capacity | 243 cm ³ |
| Fuel | Diesel EN 590 |
| Fuel consumption | 0.40 L/hr |
| Tank capacity | 3.00 l |
| Starter type | Recoil starter |
| Engine Manufacturer | Hatz |