



BS50-2PLUS 11IN HA US

2-stroke rammers of the Plus series

Always the perfect mix: Rammers of the Plus series

Two-cycle rammers by Wacker Neuson have long been the standard in the construction industry. They are robust, rugged and designed for maximum productivity, performance and durability. The two-stroke tamper offers high compaction performance and ease of operation that convinces every day. It is powered by the WM80 engine developed specially by Wacker Neuson, which thanks to its catalytic converter is well below all emissions standards. The rammers of the Plus series are equipped with separate oil lubrication, which automatically ensures that the fuel is always mixed in the optimum ratio.

Highlights

- Separate, extra large oil tank
- Intelligent, electronic automatic low oil shutoff (2Plus vibratory rammer)
- Automatic idling shutdown
- Optimized starting and operating performance
- Individual setting of the carburetor
- 2-stroke engine
- Just one lever for starting, idling and stopping
- Large stroke, high impact force
- Fast travel speed
- 4-stage air cleaner (cyclone, paper filter and 2 foam air cleaners)

Technical Data

Mechanical - Output Details

Number of blows	687.0 1/min
Area capacity	1,711.5 ft ² /h
Forward Running	0.5 fps
Power of impact	3,596.9 lbf

Mechanical Details

Length	26.5 "
Length Ramming Shoe	13.4 "
Width	13.5 "
Width Ramming Shoe	11.0 "
Height	37.0 "
Weight	130.07 lb
Operating weight	130.1 lb

Stroke at tamper 2.5 "

Environment Data

Operating temperature range	14 - 104 °F
Sound power LWA, guaranteed	108.0 dB(A)
Sound power LWA (Standard)	• EN 500-4
HAV summation (average value)	29.2 ft/s ²
HAV summation (Standard)	• EN 500-4

Electrical System

Display Equipment	• Operating hours counter
Operating elements	• Pushbutton OFF

Operating Fluids

Oil specification	• SAE 10W-40
Oil volume	0.185 gal US