



RC110P

Drum roller

Powerful compaction on any terrain

Perfect view in all directions makes work with the Wacker Neuson single drum soil compactors safer and comfortable. Because of the compact design, the operator always has the working area and the drums in view from his seat. With a large departure angle and outstanding gradeability, it is easy to maneuver even on uneven terrain. The simple operation via an intuitively-designed display and joystick makes working easier and ensures that the operator is familiar with the machine in no time.

Highlights

- Padded (sheepsfoot) drum
- Ergonomic work platform
- Uniform operating concept
- Large line-of-sight, compact construction

Technical Data

■ Mechanical - Output Details

Gradeability	57.0 %
Gradeability max. (without vib)	62.0 %
Travel speed	0.0 - 12.0 km/h
Compaction force I (front)	310 kN
Compaction force II(front)	200 kN
Compaction force I (rear)	53 kN
Compaction force II(rear)	53 kN
Vibration frequency I (front)	30.0 Hz
Vibration frequency II (front)	36.0 Hz
Amplitude Level I (front)	1.9000 mm
Amplitude Level II (front)	0.8000 mm
Centrifugal force I (front)	246 kN

Ground clearance Middle	390.0 mm
Turning radius inside	3,870.0 mm
Operating weight with roll-ove	11,725.0 kg
Operating weight with cabin	11,975.0 kg
Wheelbase	3,150.0 mm
Ramming shoes (Number)	140.0
Operating weight, max.	13,110.00 kg
Curb clearance (left)	510.0 mm
Curb clearance (right)	510.0 mm
Surface of the pad feet	152.0 cm ²
Total height with cabin	2,960.0 mm
Empty weight with cabin	11,760.0 kg
Empty weight with ROPS	11,510.0 kg
Slope angle (front)	53.0 °
Slope angle (rear)	32.0 °
Turning radius outside	6,120.0 mm

■ Mechanical Details

Length	5,850.0 mm
Height Ramming shoe	100.0 mm
Operating weight	11,975.0 kg
Dry Weight	11,760.0 kg
gross vehicular weight	12,110.0 kg
Curb clearance right	71.0 mm
Curb clearance left	71.0 mm
Operating width	2,140.0 mm

■ Engine

Cylinder capacity	3,621.0 cm ³
Effective power	85.0 KW
Nominal Engine speed	2,300.0 1/min
Standard (Effective power)	ISO 14396
Starter battery Voltage	12.0 V

Battery capacity (nom. value)	152.0 Ah	CO2 (NRTC)	730.8 g/KWh
Engine Manufacturer	Deutz	PM (NRTC)	0.0 g/KWh
Engine Designation	TCD 3.6 L4	■ Operating Fluids	
■ Environment Data			
Sound level LpA	88.0 dB(A)	Tank capacity AdBlue®/DEF	32.0 l
Sound power LWA, measured	102.0 dB(A)	Fuel Tank capacity	280.0 l
Sound power LWA, guaranteed	104.0 dB(A)	■ Chassis	
Exhaust aftertreatment	DOC-SCR	Pendulum angle +/-	10.0 °
Catalyst	yes	Width over tires (rear)	2,160.0 mm
Particle filter	no	Number of tires (rear)	2.0
CO (NRTC)	0.0 g/KWh	Wheel size (rear)	TR 23.1-26 12 PR
		Wheel load per tire (rear)	2,712.5 kg