



PS2-500

Submersible Pump

Heavy-duty and durable for demanding dewatering tasks

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Highlights

- Variety of models
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Oil lifter for reliable lubrication in any situation
- Safe to run dry
- Steel sleeve reduces wear of the shaft

Technical Data

■ Electrical - Output Details

| | |
|-------------------|---------|
| Nominal current | 2.90 A |
| Nominal voltage | 230.0 V |
| Nominal frequency | 50.0 Hz |
| Phase | 1.0 ~ |

Width 185.0 mm

Height 355.0 mm

Operating weight 10.4 kg

Intake-/Pressure socket-dia. 50.0 mm

■ Motor

Nominal speed 3,000.0 1/min

■ Electrical System

Length Cable 10.0 m

Cable cross-section 1.0 mm²

■ Mechanical - Output Details

| | |
|----------------------|-------------|
| Flow rate max. | 225.0 l/min |
| Solid diameter max. | 6.0 mm |
| Delivery height max. | 11.0 m |

■ Mechanical Details

| | |
|--------|----------|
| Length | 185.0 mm |
|--------|----------|