



E12540B

Hydronic Heater

easy to transport, simple to use hydronic heater.

The E 1250 was designed with the safety features you require and the simple, intelligent operation you desire. All operator interface points are conveniently located in the rear of the machine for simplified operation. Our new concrete cure mode simplifies the guesswork in maintaining proper concrete temperature, and our user-friendly control panel incorporates a watchdog circuit, E-Stop, and single point reset for the most common faults. All versions are telematics ready.

Highlights

- Powerful positive displacement pumps

Technical Data

■ Electrical - Output Details

Nominal current 15.00 A

Nominal voltage 120.0 V

Display Equipment

Performance monitoring light

■ Mechanical Details

Length 3,556.0 mm

Gross Axle Weight Rating 1,814.0 kg

Width 1,930.0 mm

Height 1,727.0 mm

Operating weight 1,440.0 kg

Dry Weight 1,238.0 kg

Gross vehicular weight 1,440.0 kg

Lift Bail - quantity 0.0

Length hose 381.0 m

■ Operating Fluids

Fuel specification Winter Blend Diesel No. 2

Run Time (75 % Prime Load) 90.0 hrs

Fuel Tank capacity 269.0 l

Utilizable tank capacity 258.0 l

Fuel Consumption no genset 3.8 L/hr

Fuel Consumption Natural Gas 66.1 l/min

Fuel Consumption Propane 5.7 L/hr

Run Time (100 %) 68.0 hrs

■ Chassis

Brake Electric brake

Hitch Type Centrifugal Clutch

Tongue Weight, min. 77.0 kg

Tongue Weight, max. 104.0 kg

Tires ST205/75R15

■ Generator

Genset no

■ Environment Data

Operating temperature range 38 - 93 °C

Sound level LpA 64.5 dB(A)

■ Shipping and Storage

Shipping weight 1,238.0 kg

Shipping weight with Trailer 1,238.0 kg

■ Electrical System

Temperature monitor digital