

PSR1 500

Submersible Pump

These high performance single-phase submersible pumps are ideal for job sites needing fast, dependable, low level water pumping.

Pump can start in low water levels when it is primed through the discharge port. No matter how large or small the job. Wacker Neuson submersible pumps offer the versatility and durability contractors need for light dewatering. Suitable for most outlets, these pumps offer big pump features for small pump investment.

MAT: 5000620411

Highlights

- Built-in thermal protection prevents motor damage
- Top discharge for continuous operation and motor cooling
- Kink-free multi-directional discharge coupling

Technical Data

Mechanical - Output Details

Flow rate max.	81.9 gal/mi
Solid diameter max.	0.2 in
Delivery height max.	59.1 Foot

Mechanical Details

Length	7.6 in
Width	8.8 in
Height	13.4 in
Operating weight	30.4 lb

Motor

Nominal power	0.75 kW
Nominal frequency	60.0 Hz
Nominal speed	3,300.0 1/min

Electrical System

Length Cable	49.2 Foot

Shipping and Storage

Length for shipping	18.7 in
Width for shipping	10.5 in
Height for shipping	10.2 in
Shipping weight	37.4 lb

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com