

# The space saver

The DT05 comes into its own in conditions where space is tight and manoeuvrability is a must. Its very compact dimensions allow driving through a normal 80cm-wide door with no problem. Easy intuitive functions ensures low service and operating costs. The powerful drive system reliably takes the machine where it needs to go, even with a full skip and operator.

### **Hydrostatic drive**



Simply start and off you go: Because of the hydrostatic drive system, no frequent gear changing is needed and the operator can focus on the task. The hydraulic drive system and the working hydraulics can be operated independently of each other.

### Hanging suspension-mounted rollers



The suspension-mounted rollers provide for a smooth and safer operating experience. Due to the suspended support, the rollers adapt to the terrain and compensate for obstacles or unevenness, such as stones. As a result, the operator benefits from optimal driving comfort, even off-road.



## Diesel or petrol engine

Diesel or petrol engines are available depending on the specifications or requirements.



### **Small dimensions**

The compact dimensions of the machine make it ideal for manoeuvring and working in confined spaces.

#### **Technical Information**

	Units	DTO5
Hydraulic		
Hydraulic pump		ZRP
Flow rate	l/min	30
Mechanical - Output Details		
Travel speed	km/h	3.9
Mechanical Details		
Length	mm	1,630
Width	mm	660
Height	mm	1,185
Payload	kg	500
Skip		Front tip skip
Skip capacity levelled	I	273
Skip capacity heaped	I	313

	Units	DTOS	
Operating weight (minmax.)	kg	495 - 620	
Engine			
Motor type		Diesel/Petrol engine	
Cylinder		1	
Cylinder capacity	cm3	320	
Effective power	KW	4.5	
Stroke	mm	67	
Bore	mm	78	
Nominal engine speed	1/min	3,600	
Manufacturer		Yanmar	
Engine designation		L70N6	
Shipping and Storage			
Shipping weight	kg	420	





