



**WACKER
NEUSON**
all it takes!



BPU 5545A US

Medium-weight reversible vibratory plates

Unbeatable on any surface

Highlights

- Sturdy and durable
- Very good accessibility to all maintenance points
- High surface performance

Technical Data

■ Mechanical - Output Details

Centrifugal force	55 kN
Area capacity	852.0 m ² /h
Forward Running	27.0 m/min
Gradeability	36.4 %
Vibrations (Hz)	69.0 Hz

■ Mechanical Details

Length Baseplate	900.0 mm
Width	604.0 mm
Width Baseplate	440.0 mm
Height	1,308.0 mm

Height Cover frame	725.0 mm
Thickness Baseplate	12.0 mm
Operating weight	350.0 kg
Underclearance	725.0 - 859.0 mm

■ Engine

Effective power	6.4 KW
Nominal Engine speed	2,600.0 1/min

■ Environment Data

HAV summation (average value)	2.5 m/s ²
HAV summation (Standard)	EN 500-4

Available engines

Honda GX390-UT2X-QA-4-SD

Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder	1
Cylinder capacity	389 cm3
Fuel	Gasoline
Fuel consumption	2 L/hr
Tank capacity	6.1 l
Effective power	6.4 KW
Nominal Engine speed	3,000 PL
Standard (Effective power)	SAE J1349
Operating power	5.4 KW
Operating Engine speed	2,600 PL
Starter type	Recoil starter
Engine Manufacturer	Honda