



**WACKER
NEUSON**
all it takes!



DPU90rLec770 US

Remote-control vibratory plate

Powerful compaction

Highlights

- Compamatic
- Compact dimensions, high performance
- Sturdy and durable
- Infra-red remote control with tried and tested safety features
- Variable, precise control

Technical Data

■ Mechanical - Output Details

Centrifugal force	20,233 lbf
Area capacity	13,928.6 ft ² /h
Forward Running	1.5 fps
Gradeability	34.0 %
Vibrations (Hz)	63.0 Hz

■ Mechanical Details

Length Baseplate	46.5 "
Width	30.3 "
Width Baseplate	30.3 "

Height	32.8 "
Height Cover frame	32.4 "
Thickness Baseplate	0.6 "
Operating weight	1,596.1 lb
Underclearance	32.7 "

■ Engine

Effective power	14.3 hp
Nominal Engine speed	3,350.0 1/min

■ Electrical System

Remote Control Range	65.6 Foot
----------------------	-----------

Available engines

Kohler KDW 702 - 3350 US

Cylinder capacity	41.9 Inch3
Fuel consumption	0.7 GPH US
Tank capacity	1.9 gal US
Effective power	14.3 PS
Operating power	13.1 PS
Cooling	Water-cooling
Engine type	Diesel engine
Engine operating mode	four-stroke
Cylinder	2
Fuel	Diesel EN 590
Standard (Effective power)	ISO 3046-1
Standard (Operating power)	ISO 3046-1
Starter type	E-starter
Engine Manufacturer	Kohler