



**WACKER
NEUSON**
all it takes!



ST11

Compact Track Loader

Versatility is the real driver of this machine

Versatile, compact and powerful, the ST11 compact track loader is designed to for a variety of construction projects. The high quality track system on the ST11 makes the unit the perfect fit for landscape projects, light site work, grading and general material handling. With an operating weight under 2.2 tonnes the unit can easily be towed to and from the job site helping to help ensure a profitable project for the owner every time.

Highlights

- Ergonomically designed operators platform
- Daily maintenance made easy
- Hydrostatic power

Technical Data

■ Hydraulic

Flow rate	40.0 l/min
Flow rate max.	70.0 l/min
Auxiliary hydraulics relief pressure	190.0 bar

■ Mechanical - Output Details

Ground Pressure	0.4 bar
Breakout force - tilt	930.0 kN
Breakout force - lift	1,030.0 N
Tractive Effort max. at 100% effective force	2,915.0 N
Travel speed stage 1	4.5 km/h
Travel speed stage 2	10.0 km/h

■ Mechanical Details

Overall Length without bucket	2,205.0 mm
Overall Length with Bucket	2,905.0 mm
Overall width without bucket	1,350.0 mm
Overall height to top of ROPS	1,950.0 mm
Bucket Hinge Pin Height	2,720.0 mm

Maximum bucket roll back at ground	24.0 °
Bucket roll back at maximum height	96.0 °
Angle of departure	26.0 °
Bucket dump height at maximum height	2,057.0 mm
Bucket dump angle at maximum height	40.0 °
Operating weight	2,220.0 kg
Track gauge	250.0 mm
Underclearance	200.0 mm
Length of Track on Ground	1,218.0 mm
Dump reach at maximum height	3,470.0 mm

■ Operating Fluids

Fuel Tank capacity	124.0 l
--------------------	---------

■ Chassis

Tip Load	1,040.0 kg
Rated Operating Capacity at 50% Tip Load	520.0 kg
Rated Operating Capacity at 35% Tip Load	400.0 kg