

PS2 500

Submersible Pump

These high performance single-phase submersible pumps are ideal for job sites needing fast, dependable, low level water pumping.

Pump can start in low water levels when it is primed through the discharge port. No matter how large or small the job. Wacker Neuson submersible pumps offer the versatility and durability contractors need for light dewatering. Suitable for most outlets, these pumps offer big pump features for small pump investment.

MAT: 5000009172

Highlights

- Top discharge for continuous operation and motor cooling
- Built-in thermal protection prevents motor damage
- Durable mechanical seals
- Heavy-duty strain relief power cord
- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

Mechanical - Output Details

Flow rate max.	62.3 gal/mi
Solid diameter max.	0.2 in
Delivery height max.	39.4 Foot

Mechanical Details

Length	7.3 in
Width	7.3 in
Height	12.0 in
Operating weight	20.9 lb

Motor

Nominal power	0.48 kW
Nominal current	3.0 A
Nominal voltage	220.0 V
Nominal frequency	60.0 Hz
Nominal speed	3,270.0 1/min

Electrical System

Length Cable	32.8 Foot

Shipping and Storage

Length for shipping	13.7 in
Width for shipping	9.8 in
Height for shipping	9.0 in
Shipping weight	28.0 lb

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com