

PT3c

Self Priming Trash Pumps of the PT series

Efficient and Durable Pump for Various Application

This self-priming centrifugal trash pump driven by a reliable Loncin engine and equipped with special cast iron impeller and volute, features performance and durability fit for any construction job-site. It is the ideal choice for pumping all kinds of dirt and trash water.

MAT: 5100079343

Highlights

- Reliable Loncin engine
- Strengthened design
- Compact Storage
- Wide impeller opening and volute channel

Technical Data

Mechanical - Output Details

Flow rate max.	1,150.0 l/min
Solid diameter max.	25.4 mm
Suction head max.	7.0 m
Delivery height max.	20.0 m

Mechanical Details

Length	678.0 mm
Width	530.0 mm
Height	535.0 mm
Operating weight	64.0 kg
Intake-/Pressure socket-dia.	80.0 mm

Engine

Tank capacity	6.0 l
Engine speed 1	3,600.0 1/min
Run Time at Engine speed 1	2.4 hrs

Environment Data

Sound power LWA, guaranteed	109.0 dB(A)
Sound power LWA (Standard)	DIN EN ISO 3744

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com