



**WACKER
NEUSON**
all it takes!



IRFU45/120/10 UK

High-frequency internal vibrators

Top Performance from every model

The IRFU high-frequency internal vibrator series are easy to use. They simply connect to the single-phase power supply and are ready to use. They offer reliable operation even when used with fluctuating generator input voltages. The Wacker Neuson IRFU high-performance internal vibrator is designed for long life and professional concrete consolidation results. It is available in many different versions. The integrated personal protection switch (Bodyguard™) offers a high standard of safety.

Highlights

- Bodyguard
- Completely tempered vibrator head
- Thermal overload protection breaker
- High-performance electric motor with stable speeds
- Switch box with integrated frequency converter

Technical Data

■ Electrical - Output Details

Nominal current	9.60 A
Nominal voltage	110.0 - 130.0 V
Nominal frequency	50.0 - 60.0 Hz
Nominal power [P]	0.88 KW
Phase	1.0 ~

■ Mechanical - Output Details

Amplitude at air	2.300 mm
Vibrations	12,000.0 1/min
Vibrations (Hz)	200.0 Hz

■ Mechanical Details

Length Hose	10.0 m
-------------	--------

Weight	21.90 kg
Rubber cap	no

■ Motor

Motor type	Asynchronous motor
------------	--------------------

■ Environment Data

Protection class	I / Protective earthing
Degree of protection	IP67

■ Electrical System

Breaker Switch On/Off	Yes
Integrated transformer	yes
Length Cable	15.0 m
Kind of plug	CEE-Plug 2P+E 16A 110V 4H