



## GV5000A

### Portable Generators of the GV series

Three performance classes for reliable power supply

The generators in the GV series are cost-effective synchronous generators offering a reliable power supply even throughout continuous operation. The GV series includes models in three different performance categories as well as AC and three-phase designs. In addition to application on construction sites, the portable generators can equally be used for industrial, commercial and agricultural applications.

## Highlights

- Sturdy protective frame
- Large tank with long running time
- Compact dimensions
- Honda four-stroke motor
- No grounding necessary

## Technical Data

### ■ Electrical - Output Details

Aggregate continuous power 1~ (COP)	3.9 KW
Aggregate maximum power (MAX)	4.0 KW

### ■ Mechanical Details

Length	729.0 mm
Width	500.0 mm
Height	536.0 mm
Operating weight	66.0 kg

### ■ Generator

Generator type	NSM K100 E
Output current 1~	17.8 A
Output voltage	230.0 V

Output frequency	50.0 Hz
Efficiency factor 1~	0.9 cos φ
Nominal speed	3,000.0 1/min
Phase	1.0 ~
Earthing system	Electrical separation

### ■ Environment Data

Degree of protection	IP23M
Sound power LWA, guaranteed	97.0 dB(A)

### ■ Electrical System

Main Circuit Breaker Rating	18.0 A
Available voltages 1~	230.0 V
Receptacle Type	2 x CEE7/3 (Typ F) 230V 16A 1~
Number of Sockets	2.0

## Available engines

### ■ Honda GX270T2-VPX6

Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder	1
Cylinder capacity	270 cm <sup>3</sup>
Fuel	Gasoline
Fuel consumption	1.60 L/hr
Tank capacity	11.00 l
Effective power	4.60 KW
Nominal Engine speed	3,000 PL
Standard (Effective power)	SAE J1349
Starter type	Recoil starter
Engine Manufacturer	Honda